Huawei Certified Network Engineer

1. Which of the following commands can be used to create node data?

A. get/node

B. create /node

C. set/node data

D. 1s/node

Answer(s): B

---

2. Which of the following is the ElasticSearch node?

A. EsNode

B. Index

C. EsMaster

D. Cluster

Answer(s): A

---

3. Which of the following is not a role or service involved in the process of reading data in HBasei?

A. HDFS

B. HRegionServer

C. LHMaster

D. ZooKeeper

Answer(s): C

---

4. Which of the following is not a state store supported by Flink( )?

A. FsStateBackend

B. RocksDBStateBackend

C. MemoryStateBackend

D. FileStateBackend

Answer(s): D

---

5. In the MRS platform, which component does the F1ume data flow not need to pass through in the node?

A. Sink

B. Channel

C. LTopic

D. Source

Answer(s): C

---

6. What component does HBase use by default as its underlying file storage system?

A. File

B. Kafka

C. Memory

D. HDFS

Answer(s): D

---

7. Which command in Redis is to view the remaining lifetime of a key?

A. persist

B. expire

C. ttl

D. expireat

Answer(s): C

---

8. Which of the following is not a core element of KrbServer?

A. KDC (Key Distribution Center)

B. Kerberos Client

C. Kerberos KDC Client

D. Kerberos KDC Server

Answer(s): C

---

9. Assuming that the amount of data is about 200GB: the maximum capacity of shards is limited to 30GB, what is the appropriate maximum number of shards?

A. 9 or 10

B. 7 or 8

C. 3 or 4

D. 5 or 6

Answer(s): B

---

10. What is the index name of ElasticSearch?

A. ddcvc

B. doc

C. logstash-2020.01.17

D. 3sDqsm8Bu-kTplzOjqhL

Answer(s): C

---

11. The following are the characteristics of Huawei Kunpeng processor

A. High-performance computing, ARM-compatible high-performance Kunpeng processors and x86-architecture servers and solutions

B. Safe and reliable, creating high quality as stable as Mount Tai

C. Open ecology, support mainstream software and hardware in the industry, and work with developers, partners and industrial organizations to create a new base for intelligent computing

D. everything abovecorrect

Answer(s): D

---

12. When installing the Streaming component of FusionlnsightHD, the Nimbus role requires several nodes to be installed

A. 3

B. 2

C. 4

D. 1

Answer(s): B

---

13. In an MRS cluster, which of the following components does Spark mainly interact with?

A. Zookeeper

B. Yarin

C. Hive

D. HDFS

Answer(s): A

---

14. In the Fusioninsight product, about the Kafka topic, which of the following descriptions are incorrect?

A. Each topic can only be divided into one partition (area)

B. The number of Topic partitions can be configured at creation time

C. The storage layer of each Partition corresponds to a log file, and the log file records all information data

D. Each message published to Kafkab has a category, which is called Topic, which can also be understood as a queue for storing messages.

Answer(s): A

---

15. When the Loader of MRS creates a job, what is the role of the connector?

A. Configure how jobs connect to external data sources

B. Configure how jobs connect to internal data sources

C. Provide optimization parameters to improve data import and export performance

D. Make sure there are conversion steps

Answer(s): A

---

16. Which of the following descriptions about Hive features is incorrect?

A. Flexible and convenient ETL

B. Only supports MapReduce computing engine

C. Direct access to HDFS files and HBase

D. Easy to use and easy to program

Answer(s): B

---

17. How many shards does an index library of ElasticSearchl have by default?

A. 5

B. 6

C. 3

D. 4

Answer(s): A

---

18. Which of the following factors contributed to the vigorous development of the era of big data?

A. Reduced hardware costs and increased network bandwidth

B. The rise of cloud computing

C. The popularization of smart terminals and the improvement of social demands

D. all of the aboveA. True

Answer(s): D

---

19. Which of the following commands can be used to clear the data of all databases under the Redis instance?

A. dropall

B. Lflushall

C. flushdb

D. dropdb

Answer(s): B

---

20. Existing server.channelsa=ch1, set the Channel type to File Channel, which of the following configurations is correct?

A. server.channels.ch1.type file

B. server.channels.chl.type memory

C. server.channels.type memory

D. server.channels.type file

Answer(s): A