

Huawei Certified Pre-sales Associate- IP Network(Datacom)-ENU

1. Which of the below is not the high-reliability technology?

A. VPN FRR

B. E-Trunk

C. IP/LDP FRR

D. IBGP

Answer(s): D

2. Which are main differences between CE12800S and CE12800?() (Multiple Choice)

A. demension size

B. the number of switching fabric

C. no orthogonal architecture

D. new line card only for CE128S

Answer(s): A B

3. Which models does S12700 compete against overseas? (Multiple Choice)

A. Cisco 3850

B. Cisco 6800

C. Cisco 4500X

D. Cisco N9000

E. HP 10500

Answer(s): B E

4. How much switching fabric slots that NE40E-X8 could support?

A. 3

B. 2

C. 4

D. 0

Answer(s): A

5. The 10GE downlink TOR switch model is ()

A. CE58XX

B. CE68XX

C. CE78XX

D. CE88XX

Answer(s): B

6. What type of switch is S3700?

A. L2 100M switch

B. L2 gigabit switch

C. L3 100M switch

D. L3 gigabit switch

Answer(s): C

7. the MAC table size of CE12800's F series line card is()

A. 256K

B. 512K

C. 750K

D. 1M

Answer(s): C

8. Which technology is recommended for data centers interconnected?

A. BGP-EVPN + VxLAN

B. SVF

C. CSS

D. iStack

Answer(s): A

9. The end-to-end service recovery time that Huawei could support is?

A. 50ms

B. 10ms

C. 3.3ms

D. 200ms

Answer(s): A

10. How many SFU slots does an S12710 have?

A. 12

B. 10

C. 4

D. 2

Answer(s): D

11. ISM (Industrial Scientific Medical) frequency band is license free, there is no authorization for using this frequency.

A. TRUE

B. FALSE

Answer(s): A

12. which encryption algorithms do AR support? (Multiple Choice)

A. SMI

B. SM2

C. SM3

D. SM4

Answer(s): A B C D

13. Which scenarios is suitable to deploy wall plate AP2050DN? (Multiple Choice)

A. Hotel

B. Dormitory

C. Hospital

D. Outdoor square

E. Shopping mall

Answer(s): A B C

14. AR550 series can be used on In-Vehicle Scenarios.

A. TRUE

B. FALSE

Answer(s): B

15. EVPN is used as control plane for Vxlan of CE switch.

A. TRUE

B. FALSE

Answer(s): A

16. Which are AR G3 key reliability technologies? (Multiple Choice)

A. Hot swap cards

B. Power module redundancy

C. Main controller redundancy

D. BFD

Answer(s): A B C D

17. What is the maximum switching capacity of S6720?

A. 480Gbps

B. 640Gbps

C. 960Gbps

D. 1.44Tbps

Answer(s): D

18. Which line card is NOT used for chassis switches?

A. XIEcard

B. EA card

C. EB card

D. EC card

Answer(s): C

19. The S12700 supports 1600W DC power module.

A. TRUE

B. FALSE

Answer(s): B

20. HP MSR950 series can map()

A. AR160

B. AR1220

C. AR510

D. AR2240

Answer(s): A
