

# Huawei Certified Solutions Expert

1. Enhanced MSTP evolved from MSTP, focusing on the technical aspects of packet service bearer Evolution is not a change in equipment.

A. TRUE

B. FALSE

**Answer(s): A**

---

2. Enhanced multi-service transport node (MSTP) equipment technical requirements, in line with standard YD/T 2486-2013 requirements

A. TRUE

B. FALSE

**Answer(s): A**

---

3. The enhanced MSTP solution not only supports the physical isolation of VC particles, but also supports ODUK particles  
Granule physical isolation

A. TRUE

B. FALSE

**Answer(s): A**

---

4. The enhanced MSTP solution does not support the 1588V2 synchronization mode.

A. TRUE

B. FALSE

**Answer(s): B**

---

5. SDH basic transmission module is STM-4

A. TRUE

B. FALSE

**Answer(s): B**

---

6. There are 32 time slots for 2M signals in SDH standard

A. TRUE

B. FALSE

**Answer(s): A**

---

7. The definition of OTN is Open transmission network.

A. TRUE

B. FALSE

**Answer(s): B**

---

8. OTU units can be used in docking with different FEC types, such as AFEC at the originating end, The receiving end uses FEC.

A. TRUE

B. FALSE

**Answer(s): B**

---

9. The maximum electrical crossover capacity of OSN 9800 U32E is 32T.

A. TRUE

B. FALSE

**Answer(s): A**

---

10. ODU0 frame rate is 1.25Gbits/s, ODU1 frame rate is 2.5Gbits/s, ODUflex frame rate is 40Gbits/s

A. TRUE

B. FALSE

**Answer(s): B**

---

11. OSN 1800 supports OTN ASON

A. TRUE

B. FALSE

**Answer(s): A**

---

12. WDM system, the noise is mainly introduced by EDFA amplifier

A. TRUE

B. FALSE

**Answer(s): A**

---

13. The name of MS-OTN is Multi-Service Optical Transport Network

A. TRUE

B. FALSE

**Answer(s): A**

---

14. Huawei WDM does not support OSNR detection at 100G wavelength

A. TRUE

B. FALSE

**Answer(s): B**

---

15. OSN9800 does not support 400G

A. TRUE

B. FALSE

**Answer(s): B**

---

16. FD online fiber monitoring does not affect customer business

A. TRUE

B. FALSE

**Answer(s): A**

---

17. SOM online transmission performance monitoring does not affect customer business

A. TRUE

B. FALSE

**Answer(s): A**

---

**18.** OSN 9800 M24 single board line side maximum rate 100G

A. TRUE

B. FALSE

**Answer(s): B**

---

**19.** OSN 9800 M24 can be used in trunk or converged networks for large-capacity, long-distance optical Transmission solution

A. TRUE

B. FALSE

**Answer(s): A**

---

**20.** Huawei access product network management supports rogue ONU detection

A. TRUE

B. FALSE

**Answer(s): A**

---