

TMOS Administration

1. Which must be sent to the license server to generate a new license?

A. the system's dossier

B. the system's host name

C. the system's base license

D. the system's purchase order number

Answer(s): A

2. What is the purpose of provisioning?

A. Provisioning allows modules that are not licensed to be fully tested.

B. Provisioning allows modules that are licensed be granted appropriate resource levels.

C. Provisioning allows the administrator to activate modules in non-standard combinations.

D. Provisioning allows the administrator to see what modules are licensed, but no user action is ever required.

Answer(s): B

3. When initially configuring the BIG-IP system using the config utility, which two parameters can be set? (Choose two.)

A. the netmask of the SCCP

B. the IP address of the SCCP

C. the port lockdown settings for the SCCP

D. the netmask of the host via the management port

E. the IP address of the host via the management port

F. the port lockdown settings for the host via the management port

Answer(s): D E

4. A site has six members in a pool. All of the servers have been designed, built, and configured with the same applications. It is known that each client's interactions vary significantly and can affect the performance of the servers. If traffic should be sent to all members on a regular basis, which loadbalancing mode is most effective if the goal is to maintain a relatively even load across all servers.

A. Ratio

B. Priority

C. Observed

D. Round Robin

Answer(s): C

5. The incoming client IP address is 205.12.45.52. The last five connections have been sent to members C, D, A, B, B. The incoming client. IP address is 205.12.45.52. The last five connections have been sent to members C, D, A, B, B. Given the virtual server and pool definitions and the statistics shown in the graphic, which member will be used for the next

connection.

VS_Web_Pool Settings		Web_Pool Parameters	
Destination:	172.160.22.3:80	Load Balancing:	Least Connections
Profiles:	TCP	Priority Group	
iRules:	None	Activation:	Less Than 2
Default Pool:	Web_Pool	Monitor:	None
Persistence:	None		

Web_Pool Member Statistics and Settings					
Member	Member Ratio	Member Priority	Outstanding Requests	Current Connections	Status
A: 10.10.20.1:80	3	5	4	56	Unknown
B: 10.10.20.2:80	3	4	4	57	Unknown
C: 10.10.20.3:80	3	5	4	54	Offline
D: 10.10.20.4:80	1	3	1	2	Unknown
E: 10.10.20.5:80	1	1	1	1	Unknown

A. 10.10.20.1:80

B. 10.10.20.2:80

C. 10.10.20.3:80

D. 10.10.20.4:80

E. 10.10.20.5:80

Answer(s): A

6. A site has six members in a pool. Three of the servers are new and have more memory and a faster processor than the others. Assuming all other factors are equal and traffic should be sent to all members, which two load-balancing methods are most appropriate. (Choose two.)

A. Ratio

B. Priority

C. Observed

D. Round Robin

Answer(s): A C

7. Which two can be a part of a pool's definition? (Choose two.)

A. rule(s)

B. profile(s)

C. monitor(s)

D. persistence type

E. load-balancing mode

Answer(s): C E

8. What is required for a virtual server to support clients whose traffic arrives on the internal VLAN and pool members whose traffic arrives on the external VLAN?

A. That support is never available.

B. The virtual server must be enabled for both VLANs.

C. The virtual server must be enabled on the internal VLAN.

D. The virtual server must be enabled on the external VLAN.

Answer(s): C

9. A standard virtual server has been associated with a pool with multiple members. Assuming all other settings are left at their defaults, which statement is always true concerning traffic processed by the virtual server?

A. The client IP address is unchanged between the client-side connection and the server-side connection.

B. The server IP address is unchanged between the client-side connection and the server-side connection.

C. The TCP ports used in the client-side connection are the same as the TCP ports server-side connection.

D. The IP addresses used in the client-side connection are the same as the IP addresses used in the server-side connection.

Answer(s): A

10. Monitors can be assigned to which three resources. (Choose three.)

A. NATs

B. pools

C. iRules

D. nodes

E. SNATs

F. pool members

G. virtual servers

Answer(s): B D F

11. A site has assigned the ICMP monitor to all nodes and a custom monitor, based on the HTTP template, to a pool of web servers. The HTTP-based monitor is working in all cases. The ICMP monitor is failing for 2 of the pool member 5 nodes. All other settings are default. What is the status of the monitor is working in all cases. The ICMP monitor is failing for 2 of the pool member 5 nodes. All other settings are default. What is the status of the pool members?

A. All pool members are up since the HTTP-based monitor is successful.

B. All pool members are down since the ICMP-based monitor is failing in some cases.

C. The pool members whose nodes are failing the ICMP-based monitor will be marked disabled.

D. The pool members whose nodes are failing the ICMP-based monitor will be marked unavailable.

Answer(s): D

12. A site would like to ensure that a given web server's default page is being served correctly prior to sending it client traffic. They assigned the A site would like to ensure that a given web server's default page is being served correctly prior to sending it client traffic. They assigned the default HTTP monitor to the pool. What would the member status be if it sent an unexpected response to the GET request default HTTP monitor to the pool. What would the member status be if it sent an unexpected response to the GET request?

A. The pool member would be marked offline (red).

B. The pool member would be marked online (green).

C. The pool member would be marked unknown (blue).

D. The pool member would alternate between red and green.

Answer(s): B

13. A site is load balancing to a pool of web servers. Which statement is true concerning BIG-IP's ability to verify whether the web servers are functioning properly or not?

A. Web server monitors can test the content of any page on the server.

B. Web server monitors always verify the contents of the index.html page.

C. Web server monitors can test whether the server's address is reachable, but cannot test a page's content.

D. Web server monitors can test the content of static web pages, but cannot test pages that would require the web server to dynamically build content.

Answer(s): A

14. The current status of a given pool is offline (red). Which condition could explain that state. Assume the descriptions below include all monitors assigned for each scenario.

A. No monitors are currently assigned to any pool, member or node.

B. The pool has a monitor assigned to it, and none of the pool members passed the test. The pool has a monitor assigned to it, and none of the pool. members passed the test.

C. The pool has a monitor assigned to it, and only some of the pool's members passed the test.

D. A monitor is assigned to all nodes and all nodes have passed the test. The pool's members have no specific monitor assigned to them.

Answer(s): B

15. You need to terminate client SSL traffic at the BIG-IP and also to persist client traffic to the same pool member based on a BIG-IP supplied cookie. Which four are profiles that would normally be included in the virtual server's definition? (Choose four.)

A. TCP

B. HTTP

C. HTTPS

D. ClientSSL

E. ServerSSL

F. Cookie-Based Persistence

Answer(s): A B D F

16. A site needs to terminate client HTTPS traffic at the BIG-IP and forward that traffic unencrypted. Which two are profile types that must be associated with such a virtual server?

(Choose two.)

A. TCP

B. HTTP

C. HTTPS

D. ClientSSL

E. ServerSSL

Answer(s): A D

17. Which three statements describe a characteristic of profiles? (Choose three.)

A. Default profiles cannot be created or deleted.

B. Custom profiles are always based on a parent profile.

C. A profile can be a child of one profile and a parent of another.

D. All changes to parent profiles are propagated to their child profiles.

E. While most virtual servers have at least one profile associated with them, it is not required.

Answer(s): A B C

18. A virtual server is defined using a source-address based persistence profile. The last five connections were A, B, C, A, C . Given the conditions shown in the graphic, if a client with IP address 205.12.45.52 opens a connection to the virtual server, which member will be used for the

connection.

All entries for the one virtual server and pool		
Persistence Values	Member	Age (Seconds)
200.10.0.0	10.10.20.1:80	63
201.12.0.0	10.10.20.3:80	43
153.15.0.0	10.10.20.2:80	76
205.12.0.0	10.10.20.4:80	300
195.64.0.0	10.10.20.3:80	22
198.22.0.0	10.10.20.5:80	176
214.77.0.0	10.10.20.1:80	43

Web_Pool Statistics					
Member	Member Ratio	Member Priority	Outstanding Layer 7 Requests	Connection Count	Status
A: 10.10.20.1:80	3	5	6	18	Available
B: 10.10.20.2:80	3	5	6	12	Available
C: 10.10.20.3:80	3	5	12	5	Disabled
D: 10.10.20.4:80	1	1	8	19	Offline
E: 10.10.20.5:80	1	1	4	9	Available

Virtual Server, Pool and Persistence Profile Settings					
VS_Web_Pool Settings		Web_Pool Settings		Source Persist Settings	
Destination	172.160.22.3:80	Load Balancing	Least Connectors	Mode	Source Address
Profile(s)	TCP	Priority Activation	Less than 2	Netmask	255.255.0.0
Pool	Web_Pool	Monitor	Done	Timeout	360 seconds
iRules	None				
Persistence	Source_Persist				

A. 10.10.20.1:80

B. 10.10.20.2:80

C. 10.10.20.3:80

D. 10.10.20.4:80

E. 10.10.20.5:80

Answer(s): B

19. How is persistence configured?

Persistence Table		
All entries for the one virtual server and pool		
Persistence Values	Member	Age (Seconds)
200.10.0.0	10.10.20.1:80	63
201.12.0.0	10.10.20.3:80	43
153.15.0.0	10.10.20.2:80	76
205.12.0.0	10.10.20.4:80	300
195.64.0.0	10.10.20.3:80	22
198.22.0.0	10.10.20.5:80	176
214.77.0.0	10.10.20.1:80	43

Web Pool Statistics					
Member	Member Ratio	Member Priority	Outstanding Layer 7 Requests	Connection Count	Status
10.10.20.1:80	3	5	6	18	Available
10.10.20.2:80	3	5	6	12	Available
10.10.20.3:80	3	5	12	5	Disabled
10.10.20.4:80	1	1	8	19	Offline
10.10.20.5:80	1	1	4	9	Available

Virtual Server, Pool and Persistence Profile Settings					
VS_Web_Pool Settings		Web_Pool Settings		Source Persist Settings	
Destination	172.160.22.3:80	Load Balancing	Least Connections	Mode	Source Address
Profile(s)	TCP	Priority Activation	Less than 2	Netmask	255.255.0.0
Pool	Web_Pool	Monitor	Done	Timeout	360 seconds
iRules	None				
Persistence	Source_Persist				

A. Persistence is an option within each pool's definition.

B. Persistence is a profile type; an appropriate profile is created and associated with virtual server.

C. Persistence is a global setting; once enabled, load-balancing choices are superseded by the persistence method that is specified.

D. Persistence is an option for each pool member. When a pool is defined, each member's definition includes the option for persistence.

Answer(s): B

20. Which cookie persistence method requires the fewest configuration changes on the web servers to be implemented correctly?

A. insert

B. rewrite

C. passive

D. session

Answer(s): A
